

DATABLAD

PP-Acrylic

Anvendelse:

PP-No noise tape er en billig pakketape som bedst egner sig til påsætning på folie.

Tapen bider sig fast efter et stykke tid.

Vi anbefaler brug af special noise reduction tape dispenser, da tapen ikke er en no-noise

PP er et miljøvenligt og billigere alternativ til PVC tape

101429 38mm x 66m Brun
101479 50mm x 66m Klar

Lagerføres:
Nej
Nej



Tages hjem på ca. 2-3 uger

Bredde: 12, 15, 19, 25, 38, 48, 50, 75mm

Længde: 30, 50, 66, 100, 132m

Farver: Brun, Klar og Hvid

Technical data sheet

Product	PP-Acrylic tape
Type	PP-film
Film thickness	0,025mm (+/- 10%)
Total thickness	0,043mm (+/- 5%)
Adhesive	Acrylic
Adhesion to steel	6,0 N / 25mm (+/- 10%)
Tensile strength lengthways	78 N / 25mm (+/- 10%)
Elongation	120% (+/- 10%)
Temperature resistance	up to +60°C

Use:

The packfilm PP-Acrylic is employed whenever ageing- and UV-stability are of importance. Because of the special glue this tape has to be pressed on carefully when being processed.

This tape consist of a biaxially stretched clear PP-film of which one side is coated with a water dissolved acrylic glue.

The above mentioned details are based on averages of all informations without guarantee. All users are obliged to examine the usability of the product of their specific requirements.