

DATABLAD

PP-Hotmelt

Anvendelse:

PP-Hotmelt tape er en glimrende pakketape som er en populær mellemkvalitet.

Vi anbefaler brug af special noise reduction tape dispenser, da tapen ikke er en no-noise

PP er et miljøvenligt og billigere alternativ til PVC tape

			Lagerføres:
101126	38mm x 66m	Brun	Ja
101426	50mm x 66m	Brun	Ja
101176	38mm x 66m	Klar	Ja
101476	50mm x 66m	Klar	ja



Kan importeres i andre farver og evt. med reklametryk

Bredde: 19, 25, 38, 48, 50 og 75mm

Længde: 50, 66, 100, 132, 330, 660 og 990m

Farver: Brun, klar og hvid

Technical data sheet

Product	PP-Hotmelt tape	
Type	PP-film	
Film thickness	0,028mm	(+/- 10%)
Total thickness	0,045mm	(+/- 10%)
Adhesive	Synthetic rubber glue	
Adhesion to steel	10 N / 25mm	(+/- 10%)
Tensile strength lengthways	100 N / 25mm	(+/- 10%)
Elongation	140%	(+/- 20%)
Temperature resistance	N/A	

Use:

The packfilm PP-Hotmelt is employed to close light and heavy cardboard boxes.

Because of the special formulation of the glue, a good tack and ageing resistance.

Therefore the tape is suitable especially for sealing different carton surfaces i. (testliner)

The above mentioned details are based on averages of all informations without guarantee.

All users are obliged to examine the usability of the product of their specific requirements.