

DATABLAD

PP-No noise acrylic

Anvendelse:

PP-No noise tape er en glimrende pakketape som er en populær mellemkvalitet.

Tapen er behandlet så den er mindre støjende.

PP er et miljøvenligt og billigere alternativ til PVC tape

			Lagerføres:
102000	38mm x 66m	Brun	Ja
102050	50mm x 66m	Brun	Ja
102025	38mm x 66m	Klar	Ja
102075	50mm x 66m	Klar	ja



Kan importeres i andre farver og evt. med reklametryk

Bredde: 6-100mm

Længde: 66, 100, 132, 660 og 990m

Farver: Brun, Klar, Hvid, Rød, Gul, Mørkegrøn, Lysegrøn, Mørkeblå og Lysegrøn

Technical data sheet

Product	PP-No noise tape
Type	PP-film
Film thickness	0,028mm (+/- 5%)
Total thickness	0,047mm (+/- 5%)
Adhesive	Acrylic
Adhesion to steel	5,75 N / 25mm (+/- 5%)
Tensile strength lengthways	110 N / 25mm (+/- 5%)
Elongation	140% (+/- 5%)
Temperature resistance	+110°C

Use:

The packfilm PP-No noise is employed whenever ageing- and UV-stability are of importance. Because of the special glue this tape has to be pressed on carefully when being processed.

This tape consist of a biaxially stretched clear PP-film of which one side is coated with a water dissolved acrylic glue and unwinds without noise.

The above mentioned details are based on averages of all informations without guarantee. All users are obliged to examine the usability of the product of their specific requirements.