

# DATABLAD

## PP-S Frost-tape

**Anvendelse:**

PP-S Frost tape er en glimrende pakketape som er populær til frostlager.

Vi anbefaler brug af special noise reduction tape dispensers, da tapen ikke er en no-noise

PP er et miljøvenligt og billigere alternativ til PVC tape

|        |            |      |             |
|--------|------------|------|-------------|
| 101175 | 38mm x 66m | Klar | Lagerføres: |
| 101475 | 50mm x 66m | Klar | Ja          |
| 101600 | 50mm x 990 | Klar | Ja          |



Kan evt. produceres i andre farver og dimensioner

**Technical data sheet**

|                                    |                    |           |
|------------------------------------|--------------------|-----------|
| <b>Product</b>                     | PP-Solvent tape    |           |
| <b>Type</b>                        | PP-film            |           |
| <b>Film thickness</b>              | 0,028mm            | (+/- 10%) |
| <b>Total thickness</b>             | 0,046mm            | (+/- 10%) |
| <b>Adhesive</b>                    | Solvent            |           |
| <b>Adhesion to steel</b>           | 5,5 N / 25mm       | (+/- 10%) |
| <b>Tensile strength lengthways</b> | 107,5 N / 25mm     | (+/- 10%) |
| <b>Elongation</b>                  | 145%               | (+/- 20%) |
| <b>Temperature resistance</b>      | -30°C up to +110°C |           |

**Use:**

The packfilm-PP-Frost is employed to close light and heavy cardboard boxes as well as for short-term pallet-securing or bundling and fixing of various items. Due to its temperature-resistance from -30° C up to +110° C this tape is suitable for processing in the deep-freezing industry as well as for goods which are to be wrapped with stretch-film later.

The above mentioned details are based on averages of all informations without guarantee. All users are obliged to examine the usability of the product of their specific requirements.